



## Timed basin faucet TEMPOR with mixer 9169

- Body made of chrome-plated brass
- High resistance to vandalism
- Spout equipped with an aerator
- Compact size
- Mechanism made of components with anti-deposit properties
- Anti-limescale system
- Exceptional durability and reliability
- Easy operation
- Simple installation
- Certified by the Polish National Institute of Hygiene
- CE Declaration of Conformity
- National Declaration of Performance

Option	For cold and hot water
Connector	2x G1/2
Mixer	Built-in, operated by lever
Design	Chrome-plated brass
Water time flow	Adjustable 7 seconds $\pm$ 3 second
Start	By means of the button
Water temperature	1-75°C
Water pressure	Min 1 bar - Max 6 bar
Contains	Battery, mounting kit for the washbasin

A time-delay washbasin faucet with a built-in mixer for hot and cold water is a modern product equipped with two flexible G1/2 connections. The body is made of brass coated with a bacteriostatic chrome finish.

A single water flow activation lasts 7 seconds  $\pm$  3 seconds. The working water pressure ranges from 1 to 6 bars, and the connection temperature ranges between 1°C and 75°C. It is worth noting that the faucet features a water regulator in the form of a built-in aerator. Additionally, non-return valves and mesh filters are included with the product.

Each washbasin faucet from the 9169 series comes with a factory assembly kit. Furthermore, the entire product is certified by the Polish National Institute of Hygiene, has a CE Declaration of Conformity, and a National Declaration of Performance.